



Spreader settings

ACCUPRO® 360ST

Settings for **Single Pass (SP)** and **Double Pass (DP)** applications

Product	SmartSpread™ setting	Spread width		Setting to deliver g/m ²									
				5 g/m ²	10 g/m ²	15 g/m ²	20 g/m ²	25 g/m ²	30 g/m ²	35 g/m ²	40 g/m ²	45 g/m ²	50 g/m ²
Greenmaster Pro-Lite Autumn *	F	3.2 m	SP			10	11	11 ½	12 ½	13	13 ½	14 ½	15
			DP			9	9 ½	10	10 ½	11		11 ½	
Greenmaster Pro-Lite Autumn Mg *	I	3.5 m	SP				9 ½	10	11	11 ½	12	12 ½	13
			DP			7 ½	8	8 ½	9	9 ½		10	
Greenmaster Pro-Lite Cold Start *	G	3.5 m	SP			10	11	12	12 ½	13 ½	14	14 ½	15
			DP			9	9 ½	10	10 ½	11	11 ½	12	
Greenmaster Pro-Lite Double K CalMag *	G	3.2 m	SP			9	9 ½	10 ½	11	11 ½	12 ½	13	14
			DP			8	8 ½	9		9 ½	10	10 ½	
Greenmaster Pro-Lite Invigorator *	G	3.2 m	SP			9 ½	10 ½	11 ½	12 ½	13	14	15	15 ½
			DP			8 ½	9	9 ½	10	10 ½	11	11 ½	
Greenmaster Pro-Lite Invigorator Plus *	F	3.0 m	SP			9	10	10 ½	11 ½	12 ½	13	13 ½	14 ½
			DP			8	8 ½	9	9 ½	10	10 ½	11	
Greenmaster Pro-Lite NK *	G	3.4 m	SP			8	9 ½	10 ½	11 ½	12	13	14	15
			DP			7	7 ½	8	9	9 ½	10	10 ½	
Greenmaster Pro-Lite Spring & Summer *	G	3.0 m	SP			8 ½	9 ½	10	11	12	12 ½	13	14
			DP			7	8	8 ½	9	9 ½		10	
Greenmaster Pro-Lite Turf Tonic *	G	3.5 m	SP			9	10	11	11 ½	12 ½	13	13 ½	14 ½
			DP			7 ½	8 ½	9	9 ½	10	10 ½	11	
Gronamic Golf	G	4.0 m	SP				12 ½	14	15 ½	17 ½	19 ½	21 ½	24 ½
			DP			9	9 ½	10 ½	11 ½	12 ½	13	14	
Gronamic Sport	G	3.5 m	SP				13	14	14 ½	16	17	18 ½	21
			DP			11	11 ½	12	12 ½	13	13 ½	14	
H2Pro TriSmart Granules NEW	H	3.6 m	SP		7# <small>*Delivers 12.5 g/m²</small>			9.5					
			DP		5# <small>*Delivers 12.5 g/m²</small>		7.5						
Landscaper Pro Triple Action	H	3.5 m	SP							11 ½			
			DP						9				

*Greenmaster Pro-Lite and Sierraform GT settings are listed separately due to variations in product density across different analyses.

The spreader settings are guidelines only. The spreader should be calibrated prior to application to ensure accuracy. The spreader settings are based on a walking speed of 5 km/hour. Walking faster or slower than 5 km/hour will alter the spread width and application rate. Exact rates are dependent upon the spreader itself and the accuracy of the person operating it.

For the latest spreader settings, please refer to the product page on the ICL website.



Spreader set

ACCUPRO® 360ST

Settings for **Single Pass (SP)** and **Double Pass (DP)** applications

Product	SmartSpread™ setting	Spread width	Setting to deliver g/m ²										
				5 g/m ²	10 g/m ²	15 g/m ²	20 g/m ²	25 g/m ²	30 g/m ²	35 g/m ²	40 g/m ²	45 g/m ²	50 g/m ²
Landscaper Pro Spring & Summer/Autumn Winter	H	4.2 m	SP				12	13	14	15	16	17	18
			DP				10	10 ½	11	11 ½	12	12 ½	13
ProTurf	H	4.2 m	SP				12	13	14	15	16	17	18
			DP				10	10 ½	11	11 ½	12	12 ½	13
Sierrablen	C	4.5 m	SP						16	17	18 ½	20 ½	23
			DP						12 ½	13	13 ½	14	15
Sierrablen Mini	F	3.5 m	SP				9	10	11 ½	12 ½	14	15 ½	16 ½
			DP						8 ½	9	9 ½	10	10 ½
Sierrablen Plus	F	4.0 m	SP					11 ½	12 ½	13 ½	14 ½	15 ½	16 ½
			DP					9	9 ½	10	10 ½	11	11 ½
Sierrablen Plus Pearl (CRF formulations)	F	3.5 m	SP					10 ½	11 ½	12	13	13 ½	14 ½
			DP						9	9 ½	10	10 ½	11
Sierrablen Plus Pearl * (Turf Starter 5-28-0)	E	4.0 m	SP				11	12	13	14	15	16	17
			DP				8 ½	9 ½	10	10 ½	11	11 ½	12
Sierraform GT * All Season	I	3.0 m	SP			9 ½	10 ½	11	12	12 ½	13	14	14 ½
			DP				8 ½	9	9 ½	10	10 ½		11
Sierraform GT * Anti-Stress	I	3.0 m	SP			9	9 ½	10 ½	11	11 ½	12 ½	13	13 ½
			DP				8	8 ½	9		9 ½	10	10 ½
Sierraform GT * K-Step	F	3.5 m	SP			9	9 ½	10 ½	11	11 ½	12 ½	13	13 ½
			DP				8	8 ½	9		9 ½	10	10 ½
Sierraform GT * Momentum	I	4.0 m	SP			11	12	13	14	15	16	17	17 ½
			DP				9 ½	10 ½	11	11 ½	12	12 ½	13
Sierraform GT * NK	I	3.0 m	SP			10	11	12	12 ½	13 ½	14	14 ½	15 ½
			DP				9	9 ½	10	10 ½	11	11 ½	12
Sierraform GT * Preseeder	I	3.7 m	SP			11	12	13	14	15	16	16 ½	17 ½
			DP				8 ½	9 ½	11	11 ½	12	12 ½	13
Sierraform GT * Spring Start	I	3.0 m	SP			10	11	12	12 ½	13 ½	14	14 ½	15 ½
			DP				9	9 ½	10	10 ½	11	11 ½	12

*Greenmaster Pro-Lite and Sierraform GT settings are listed separately due to variations in product density across different analyses.

The spreader settings are guidelines only. The spreader should be calibrated prior to application to ensure accuracy. The spreader settings are based on a walking speed of 5 km/hour. Walking faster or slower than 5 km/hour will alter the spread width and application rate. Exact rates are dependent upon the spreader itself and the accuracy of the person operating it.

For the latest spreader settings, please refer to the product page on the ICL website.



Spreader settings

ACCUPRO® 360ST

Settings for **Single Pass (SP)** and **Double Pass (DP)** applications

Product	SmartSpread™ setting	Spread width		Setting to deliver g/m ²									
				5 g/m ²	10 g/m ²	15 g/m ²	20 g/m ²	25 g/m ²	30 g/m ²	35 g/m ²	40 g/m ²	45 g/m ²	50 g/m ²
Sierraform GT Spring & Summer CalMag	F	3.5 m	SP			9 ½	10	11	11 ½	12	13	13 ½	14
			DP			8 ½	9	9 ½	10		10 ½	11	
Sportsmaster	G	4.0 m	SP				9 ½	10 ½	11 ½	12 ½	13 ½	14 ½	15 ½
			DP			6 ½	7 ½	8	8 ½	9 ½	10	10 ½	
Sportsmaster Renovator Pro	H	3.5 m	SP							11 ½			
			DP						9				
Sportsmaster Cleanrun Pro	H	3.5 m	SP							11 ½			
			DP						9				
Sportsmaster Base	I	4.0 m	SP				8 ½	9 ½	10 ½	11 ½	12 ½	13 ½	15
			DP			6 ½	7	7 ½	8	8 ½	9	9 ½	
Sportsmaster CRF	C	4.0 m	SP						17	18	19 ½	21 ½	
			DP						14	14 ½	15	15 ½	16
Sportsmaster CRF Mini	H	4.0 m	SP				12	13	14	15	15 ½	16 ½	17 ½
			DP				9	10	10 ½	11	12	12 ½	13
STEP Hi Mag	G	4.0 m	SP	8	9	10							
			DP	7 ½	8	8 ½							

The spreader settings are guidelines only. The spreader should be calibrated prior to application to ensure accuracy. The spreader settings are based on a walking speed of 5 km/hour. Walking faster or slower than 5 km/hour will alter the spread width and application rate. Exact rates are dependent upon the spreader itself and the accuracy of the person operating it.

For the latest spreader settings, please refer to the product page on the ICL website.